Kansas Department of Health and Environment Proposed Amended Regulation

Kansas Dry Cleaner Environmental Response Act

- 28-68-1. Definitions. For the purposes of these regulations article 68, the following terms shall be defined as follows. (a) "Applicant" means any person or governmental entity that applies to the drycleaning facility release trust fund.
- (b) "Contaminated <u>drycleaning dry-cleaning</u> site" has the meaning <u>set out specified</u> in K.S.A. <u>1995</u> <u>Supp.</u> 65-34,148, <u>subsection (h) and amendments thereto</u>.
- (b)(c) "Drycleaning Dry-cleaning waste" means waste, including drycleaning dry-cleaning wastewater, which that is generated at a drycleaning dry-cleaning facility and which that contains drycleaning dry-cleaning solvent.
- (c)(d) "Drycleaning Dry-cleaning wastewater" means separator water and all other water which that is generated during the drycleaning dry-cleaning process and contains drycleaning dry-cleaning solvents.
- (d)(e) "Existing dry-cleaning facility" means a dry-cleaning dry-cleaning facility that was in operation on or before the effective date of these regulations January 3, 1997.
- (e)(f) "Floor drain" means any opening which that is less than three inches above the floor surface and which leads to a septic tank, storage tank, sanitary sewer, storm sewer, or soils or waters of the state.

 An opening sealed with a removable seal which that prevents drycleaning dry-cleaning solvent and drycleaning dry-cleaning wastewater from entering the opening shall not be considered a floor drain.

(f)(g) "Hazardous waste" has the meaning set out specified in 40 C.F.R. part 261, subpart subparts

C and D, as in effect on July 1, 1995 1999, and hereby adopted by reference.

(g)(h) "New drycleaning dry-cleaning facility" means a drycleaning dry-cleaning facility that begins operation after the effective date of these regulations January 3, 1997.

(h)(i) "Secondary containment structure" means a tank, tray, containment pallet, containment basin, a floor surface contained within a dike and the dike proper, or a similar structure which that is designed to contain spills and leaks from drycleaning dry-cleaning units, drycleaning dry-cleaning solvent storage areas, or drycleaning dry-cleaning waste storage areas. (Authorized by and implementing K.S.A. 1995 1999 Supp. 65-34,143; effective Jan. 3, 1997; amended P-________.)